



Morning Star Pattern

PASSIVE CRAWL SPACE FOUNDATION VENTS

MODEL 950-8303 - Morning Star 18" x 10" 20 Gauge Galv. Steel MODEL 950-8304 - Steel Diamond 18" x 10" 20 Gauge Galv. Steel

DESCRIPTION

Tjernlund UnderAire™ Series Crawl Space Foundation Vents are designed to allow circulation of fresh outdoor air underneath homes and porches. Excessive humidity levels in crawl spaces is the leading cause of premature rotting of support columns, joists, floors and beam supports. Humidity can promote fungus growth and increased termite activity. Humidity may also cause plumbing failures due to rust and corrosion. Pair with Tjernlund UnderAire™ Powered Crawl Space Ventilators (Models V1, V1D, and V2D) to increase crawl space ventilation rates and automatically control humidity levels.

TOOLS REQUIRED

- 5/16" Nut Runner or Flat Head Screw Driver
- Drill with 5/16" Masonry Bit if mounting on brick or foundation block

INSTALLATION

Mount Crawl Space Vents on the inside or outside of the crawl space foundation ventilation openings. If also installing Tjernlund Powered Crawl Space Ventilators install vents on the outside of the foundation and the ventilators on the inside.

NOTE: If painting of vent is desired, use an appropriate galvanized primer/paint.

- 1. Remove existing doors or covers on ventilation openings around the perimeter of the building.
- 2. Position the vent over the ventilation opening.
- 3. If installing on foundation block or brick, mark location in the four corners of the metal face plate and drill 5/16" holes with a masonry bit. Install wall anchors into openings and secure vent to the wall with provided screws. If installing on a wood header or rim joist secure vent with provided screws in the four corners of the metal face plate.

TJERNLUND POWERED CRAWL SPACE VENTILATORS COMPLIMENT OUR PASSIVE FOUNDATION VENTS

Visit www.tjernlund.com for complete information on Tjernlund UnderAire™ Crawl Space Ventilators







P/N: 8504167

MODEL V1	MODEL V1D	MODEL V2D
One fan and small faceplate for ventilation openings through brick foundations. (Requires switch or dehumidistat to activate. Multiple ventilators may be controlled by a single switch or dehumidistat). Includes low limit thermostat.	stat, dehumidistat and pre-wired 6' power cord.	Two fans and large faceplate sized for ventilation openings through block foundations. Includes low limit thermostat, dehumidistat and pre-wired 6' power cord.

WARRANTY

TJERNLUND LIMITED ONE YEAR WARRANTY

Tjernlund Products, Inc. warrants to the original purchaser of this product that the product will be free from defects due to faulty material or workmanship for a period of (1) year from the date of original purchase or delivery to the original purchaser, whichever is earlier. Remedies under this warranty are limited to repairing or replacing, at our option, any product which shall, within the above stated warranty period, be returned to Tjernlund Products, Inc. at the address listed below, postage prepaid. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF, AND TJERNLUND PRODUCTS, INC. EXPRESSLY DISCLAIMS LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF THIS PRODUCT. THIS WARRANTY IS IN LIEU OF ALL OTHER EXPRESS WARRANTIES AND NO AGENT IS AUTHORIZED TO ASSUME FOR US ANY LIABILITY ADDITIONAL TO THOSE SET FORTH IN THIS LIMITED WARRANTY. IMPLIED WARRANTIES ARE LIMITED TO THE STATED DURATION OF THIS LIMITED WARRANTY. Some states do not allow limitation on how long an implied warranty lasts, so that limitation may may not apply to you. In addition, some states do not allow the exclusion or limitation of incidental or consequential damages, so that above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state. Send all inquires or products requiring warranty work to Tjernlund Products, Inc. 1601 9th Street, White Bear Lake, MN. 55110-6794 (651) 426-2993.